

TRANSMISSION PROPERTIES AND ELECTRICAL SPECIFICATIONS

FREQ.	Insertion Loss	NEXT	PS NEXT	ACR-F	PS ACR-F	RL	Delay	TCL	EL TCL	PS ANEXT	PS AACR-F
MHz	dB/100m	dB	dB	dB/100m	dB/100m	dB	nS/100m	dB	dB	dB	dB
	Max	Min	Min	Min	Min	Min	Max	Min	Min	Min	Min
1	2.08	75.30	73.30	68.00	65.00	20.00	570.00	40.00	35.00	67.00	67.00
10	5.93	60.30	58.30	48.00	45.00	25.00	545.38	40.00	15.00	67.00	58.20
20	8.38	55.78	53.78	41.98	38.98	25.00	542.05	36.99	8.98	67.00	52.18
25	9.38	54.33	52.33	40.04	37.04	24.32	541.20	36.02	7.04	67.00	50.24
30	10.29	53.14	51.14	38.46	35.46	23.77	540.57	35.23	5.46	67.00	48.66
62.5	14.99	48.36	46.36	32.08	29.08	21.54	538.55	32.04	NS	65.56	42.28
100	19.14	45.30	43.30	28.00	25.00	20.11	537.60	30.00	NS	62.50	38.20
200	27.58	40.78	38.78	21.98	18.98	18.00	536.55	26.99	NS	57.98	32.18
250	31.07	39.33	37.33	20.04	17.04	17.32	536.28	26.02	NS	56.53	30.24
300	34.27	38.14	36.14	18.46	15.46	17.30	536.08	25.23	NS	55.34	28.66
400	40.05	36.27	34.27	15.96	12.96	17.30	535.80	23.98	NS	53.47	26.16
500	45.26	34.82	32.82	14.02	11.02	17.30	535.61	23.01	NS	52.02	24.22

Characteristic Impedance	100±6 Ohm @ 1-500 MHz
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Cap. Unbalance (Wire to Ground)	1500 pF/Km max. @ 1 KHz.
Voltage Rating	72 Vdc max.
Dielectric Strength	1500 Volts/1 minute min rms
Velocity of Propagation (NVP)	78-80%
Propagation Delay Skew	45 nS/100m max @ 1-500 MHz
Insulation Resistance	5000 MegaOhm•Km min. @ 500 Vdc
Coupling Attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100) @100-500 MHz
Transfer Impedance	10 mOhm/m max @ 1-10 MHz 30 mOhm/m max @ 30 MHz

ORDERING INFORMATION

HCS P/N	Description	OD mm	Weight Kg/Km	Packaging	Notes
H6A-00439-DK	4x2x23# U/FTP CAT 6A Outdoor Black	9.3	72	305m Drum	-
H6A-00439-DP	4x2x23# U/FTP CAT 6A Outdoor Black	9.3	72	500m Drum	-
H6A-00439-DM	4x2x23# U/FTP CAT 6A Outdoor Black	9.3	72	1000m Drum	-