

İLETİM DEĞERLERİ VE ELEKTRİKSEL ÖZELLİKLER

FREQ.	Min. NEXT					Min RL
MHz	dB					dB
	1 m cord	2 m cord	3 m cord	5 m cord	10 m cord	
1.0	65.0	65.0	65.0	65.0	65.0	19.8
100	47.2	46.8	46.4	45.1	44.2	18.0
250	39.5	39.2	39.0	38.0	37.6	14.0
600	28.1	28.3	28.6	28.9	29.6	10.2
1000	19.8	20.4	20.7	21.7	22.8	10.0
2000	8.6	9.6	9.9	11.1	12.0	8.0

Empedans Karakteristiği	100±6 Ohm @ 1-2000 MHz
Kontak Direnci	20 mOhm max.
Direnç dengesizliği	2% max.
Voltaj Değeri	72 Vdc max.
Dielektrik kuvvet	1000 Volts/1 dakika min rms
Akım	1.0 Amps max.
İzolasyon direnci	500 MOhm min. @ 500 Vdc
Birleşim Zayıflaması	55 dB min @ 30-100 MHz 55-20log (f/100)@100-250 MHz
Transfer Empedansı	10mOhm/m max @1-10 MHz 30 mOhm/m max @30 MHz

SİPARİŞ BİLGİLERİ

HCS P/N	Açıklama	Uzunluk (m)
T08-00480-05	4 Perli 26 AWG S/FTP CAT 8 LSOH FT Patch Cord Gray	0.5
T08-00480-10	4 Perli 26 AWG S/FTP CAT 8 LSOH FT Patch Cord Gray	1.0
T08-00480-20	4 Perli 26 AWG S/FTP CAT 8 LSOH FT Patch Cord Gray	2.0
T08-00480-30	4 Perli 26 AWG S/FTP CAT 8 LSOH FT Patch Cord Gray	3.0
T08-00480-50	4 Perli 26 AWG S/FTP CAT 8 LSOH FT Patch Cord Gray	5.0
T08-00480-A0	4 Perli 26 AWG S/FTP CAT 8 LSOH FT Patch Cord Gray	10.0
T08-0A480-05	4 Perli 26 AWG S/FTP CAT 8 LSOH Patch Cord Gray	0.5
T08-0A480-10	4 Perli 26 AWG S/FTP CAT 8 LSOH Patch Cord Gray	1.0
T08-0A480-20	4 Perli 26 AWG S/FTP CAT 8 LSOH Patch Cord Gray	2.0
T08-0A480-30	4 Perli 26 AWG S/FTP CAT 8 LSOH Patch Cord Gray	3.0
T08-0A480-50	4 Perli 26 AWG S/FTP CAT 8 LSOH Patch Cord Gray	5.0
T08-0A480-A0	4 Perli 26 AWG S/FTP CAT 8 LSOH Patch Cord Gray	10.0